



Samtack
Industrial Adhesives

UV Varnish

UV curing varnish

Cardboard, paper and plastic overprint

PROPERTIES	GLOSS	GLOSS/STAMPABLE	MATT
STANDARD	UVILACK B-810	UVILACK F-820/75 E	UVILACK M-602 UVILACK M-603
BENZOPHENONE FREE	UVILACK E-505	UVILACK E-506 E	UVILACK M-606
LOW MIGRATION	UVILACK E-510	UVILACK E-511 E	-
LOW FRICTION	UVILACK F-207 A/A UVILACK F-207 A+ UVILACK E-512	-	-

UV curing flexo varnish

Cardboard, paper and plastic overprint

PROPERTIES	GLOSS	GLOSS/STAMPABLE	MATT
STANDARD	UVILACK F-820	UVILACK F-820/30 E UVILACK F-820/75 E UVILACK F-820/100 E	UVILACK M-602 UVILACK M-603
BENZOPHENONE FREE	UVILACK E-505	UVILACK E-506 E	UVILACK M-606
LOW MIGRATION	UVILACK E-510	UVILACK E-511 E	-
LOW FRICTION	UVILACK F-207 A/A UVILACK F-207 A+ UVILACK E-512	-	-

UV Cured Flexo Lamination Adhesive

(OPP/OPP) (OPP/PET) (OPP/Paper)(OPP/Met.OPP)

REFERENCE	VISCOSITY (mPa·s, 25 °C, 20 rpm)
UVILACK A-701	300 - 800
UVILACK A-702	1000 - 2000
UVILACK A-703	2000 - 3000

Screen Printing UV varnish

Viscosity Recomended mesh (threads/cm)	Standard (Board/Paper/Plastic)	High adhesión (Plastic)	High exigency
60 – 100 sec 150 – 180 threads/cm	UVILACK S-304/80 (2 faces) UVILACK S-830 (1 face)	UVILACK S-314/80	UVILACK S-307/80
100 – 140 sec 100 – 150 threads/cm	UVILACK S-304/120	UVILACK S-314/120	UVILACK S-307/120
140 – 180 sec 77 – 100 threads/cm	UVILACK S-304/160	UVILACK S-314/160	UVILACK S-307/160

Barniz serigrafía brillo curado UV

Relieve – Braille
(5.000 – 6.000 mPa·s)
23 – 55 threads/cm

UVILACK S-315

MATT (80 - 120 sec)
120 – 165 threads/cm

UVILACK S-316 M





Cerámica, 3 -Pol. Ind. Magarola Sud
08292 Esparreguera (Barcelona) Spain

www.samtack.es

Tel. + 34 93 770 84 89

Fax + 34 93 777 75 65

samtack@samtack.es